

LED strip KWP-14KCR-0480-24

Ref. KWP-14KCR-0480-24



Dimensions: Width [W]: 16.7 mm | Max run length [L]: 9 m | Cut every [C]: 100 mm | LED spacing [D]: 14.29 mm



- CRI 95+
- Excellent color rendering
- For the construction of sealed lighting fixtures

TECHNICAL SPECIFICATIONS

IP protection rating	65
Sealing type	silicone sleeve
CRI	95
Working temperature	-20°C - 60°C
Input voltage	24 V DC
Power consumption	4.8 W/m
Beam angle	120°
MacAdam's ellipse	3 SDCM
Length [L]	5000 mm
Number of LEDs per 1 m	70
Number of LEDs per cut section	7 pcs
Energy consumption	4.8 kWh/1000h
Warranty [months]	48

Color temperature	Lumen output	Efficiency	Ref
2700 K	395 lm/m	82 lm/W	KWP-14KCR27-0480-24
3000 K	432 lm/m	90 lm/W	KWP-14KCR30-0480-24
3500 K	446 lm/m	92 lm/W	KWP-14KCR35-0480-24
4000 K	472 lm/m	98 lm/W	KWP-14KCR40-0480-24
5000 K	474 lm/m	98 lm/W	KWP-14KCR50-0480-24