


LED strip KWP-8KCR-0960-24

Ref. KWP-8KCR-0960-24



Dimensions: Width [W]: 10 mm | Max run length [L]: 5 m | Cut every [C]: 50 mm | LED spacing [D]: 7.14 mm



- CRI 95+
- Excellent color rendering
- For the construction of sealed lighting fixtures

TECHNICAL SPECIFICATIONS

IP protection rating	65
Sealing type	silicone sleeve
CRI	95
Working temperature	-20°C - 60°C
Input voltage	24 V DC
Power consumption	9.6 W/m
Beam angle	120°
MacAdam's ellipse	3 SDCM
Number of LEDs per 1 m	140
Number of LEDs per cut section	7 pcs
Energy consumption	9.6 kWh/1000h
Warranty [months]	48

Color temperature	Lumen output	Efficiency	Ref
2700 K	795 lm/m	82 lm/W	KWP-8KCR27-0960-24
3000 K	865 lm/m	90 lm/W	KWP-8KCR30-0960-24
3500 K	893 lm/m	93 lm/W	KWP-8KCR35-0960-24
4000 K	944 lm/m	98 lm/W	KWP-8KCR40-0960-24
5000 K	953 lm/m	99 lm/W	KWP-8KCR50-0960-24